



CYLINDER SIZE	STRAP PART NO.	DIM. "A"		DIM. "B"		DIM. "C"		DIM. "D"		DIM. "E"		DIM. "F"	
		U.S.	METRIC	U.S.	METRIC	U.S.	METRIC	U.S.	METRIC	U.S.	METRIC	U.S.	METRIC
50 Lb.	C70-211	11"	280 mm	10"	254 mm	4-3/8"	111 mm	8-3/8"	213 mm	8-1/2"	216 mm	33-3/4"	857 mm
75 Lb.	C70-212	11-3/4"	299 mm	10-3/4"	272 mm	4-3/4"	121 mm	9-1/8"	232 mm	9-1/4"	235 mm	36-3/4"	933 mm
100 Lb.	C70-213	13"	330 mm	12"	305 mm	5-3/8"	137 mm	10-3/8"	264 mm	10-1/2"	267 mm	38"	965 mm

* All dimensions are approximate

APPLICATION

Cylinder straps are used to secure the cylinder in place, on a single cylinder system, in accordance with OSHA and NFPA 12 requirements. The straps may be secured to any structurally solid surface. Anchoring into plaster or any other facing material is not acceptable.

DESCRIPTION

Cylinder Straps are made of steel, primed and painted red with a baked enamel finish for corrosion resistance. All mounting hardware is supplied by the system installer.

MATERIALS: Carbon Steel
Paint - Red Gloss Enamel

This page intentionally left blank