



DUCT DETECTORS

DESCRIPTION

The 63-028, -029, -030, -031, 67-029 and 67-030 duct detectors are the latest in analog and conventional (4-wire) duct detection. All models incorporate Fike NS sensor technology for advanced detection. The analog duct detector allows additional features such as user selectable alarm levels, pre-alarm, alarm verification and drift compensation.

SPECIFICATIONS/OPTIONS

All Models

- Include duct housing and detector
- Terminal blocks accept up to 14 AWG wire
- Form C relays rated 10A - 115V
Form A relay rated 1A - 24V
- Compatible with sampling tubes:

02-4630	2.5 ft
02-4631	5.0 ft
02-4632	10.0 ft

Analog Models

- Operates on the Cheetah digital signal line circuit
- Uses NS analog photo detector
- Detector can be adjusted for alarm level sensitivities between 0.9 to 2.7%/ft obscuration
- Pre-alarm level can be set as low as 0.1%/ft obscuration
- 63-028 - Base model
- 63-029 - Same as 63-028 except provides:
 - Remote alarm and remote pilot LED outputs
 - One Form C alarm relay
 - One Form C trouble relay
 - Provides input for remote test switch
 - Requires separate 24Vdc power source

Conventional (4-wire) models

- Can be magnet tested without removing the housing cover
- Provides one each; Form C alarm relay, Form C trouble relay, and Form A alarm relay
- Provides outputs for alarm LED and pilot LED
- Provides input for remote test and remote reset switch
- Operates on 24Vdc or 24Vac. Additionally, each model has a 115Vac or 230Vac input
- 63-030 - photo detector, 115Vac
- 63-031 - photo detector, 230Vac
- 67-029 - ion detector, 115Vac
- 67-030 - ion detector, 230Vac

(This page is left blank intentionally)



Copyright © Fike Corporation All Rights Reserved.

Form No. P.1.14.01-1 July, 2005 Specifications are subject to change without notice.
