



DUCT DETECTOR REMOTE ACCESSORIES

DESCRIPTION

The NS Duct Detector Remote Accessories are designed to be used with the Conventional and Analog Duct Detectors to provide audible and visual indication as well as remote test/reset functions.

These devices are constructed of brushed stainless steel and mount on a standard single or double gang backbox.

SPECIFICATIONS

Power Requirements (provided by Duct Detector)

Alarm LED	15 ma
Pilot LED	15 ma
Horn	20 ma @ 24 VDC

Sound Pressure

Horn	78 db @ 10 feet
------	-----------------

Dimensions

Single Gang	2.75" (69.85mm) W
	4.5" (114.3mm) H
Double Gang	4.5" (114.3mm) W
	4.5" (114.3mm) H

P/N 63-034

Function:

Remote Alarm LED (red)

For use with:

63-030, 67-029, 63-031, 67-030, 63-028, 63-029

P/N 63-036

Function:

Remote Alarm LED (red)

Key-Operated Test/Reset Switch

For use with:

63-030, 67-029, 63-031, 67-030, 63-029

P/N 63-035

Function:

Remote Alarm LED (red)

Pilot LED (green)

For use with:

63-030, 67-029, 63-031, 67-030, 63-029

P/N 63-037

Function:

Remote Alarm LED (red)

Pilot LED (green)

Key-Operated Test/Reset Switch

For use with:

63-030, 67-029, 63-031, 67-030, 63-029

P/N 63-038

Function:

Remote Alarm Horn

Remote Alarm LED (red)

Pilot LED (green)

Key-Operated Test/Reset Switch

For use with:

63-030, 67-029, 63-031, 67-030

(This page is left blank intentionally)



Copyright © Fike Corporation All Rights Reserved.
Form No. P.1.22.01 July, 2005 Specifications are subject to change without notice.
